

AT
SERIES 系列

High-end plug & play LED TV 高端户内外一体机



AT SERIES

- Mirror server function
- Touch screen
- Electric rising & lowering available
- Easy to use with plug-n-play design
- Support WIFI, 4G, network control
- Support remote control
- IP65 for outdoor version
- Support USB, HDMI input
- Support multiple video format

- 投屏功能
- 可触控屏幕
- 底座带电子升降系统
- 即插即用，方便快捷
- 支持WiFi，4G，网线控制
- 支持远程集成控制
- 户外版本防护等级IP65



前维护
Front Access



高度可调节
Height adjustable



租赁
Rental



超薄
Ultra Slim



静音
Noise Free



高清
High Definition

FEATURES 特性



Multiple installation 多种安装方式

SPECIFICATIONS 详细参数

参数	Parameter	Unit	AT1.9i	AT2.5i	AT1.9	AT2.5
像素间距	Pixel pitch	mm	1.995	2.571	1.995	2.571
亮度	Brightness	nits	800	1000	2500-3000	3000-4000
像素组成	Pixel configuration	R/G/B	SMD 3 in 1			
色温	Colour temperature	deg.K	6500			
水平视角	Viewing angle-Horizontal (50% brightness)	deg.	160（+80/-80）			
垂直视角	Viewing angle-Vertical (50% brightness)	deg.	140（+70/-70）			
推荐最小观看距离	Recommended minimum viewing distance	m	1.9	2.5	1.9	2.5
箱体宽度	Panel width	mm	2355		2385	
箱体高度	Panel height	mm	1348		1408	
箱体厚度	Panel depth	mm	90		105	
箱体面积	Panel area	m²	3.1745		3.3581	
箱体材料	Panel material		Alloy Aluminum（型材铝）			
箱体重量	Panel weight	Kg	120		180	
防护等级（前/后）	Ingress protection (front/rear)	IP	41/30		65/54	
箱体像素矩阵	Pixel matrix per panel		1152x648	896x504	1152x648	896x504
亮度控制	Brightness control		255			
数字处理	Digital processing	bit	14			
视屏帧频	Frame rate	Hertz	50~60			
视频刷新	Display refresh rate	Hertz	2880			
输入电压	Input voltage	VAC	100~240			
输入电源频率	Input power frequency	Hertz	50~60			
输入最大功耗	Input power (Max.)	W/m²	536	504	473	473
输入额定功耗	Input power (Avg.)	W/m²	187	176	165	165
工作环境	Operating temperature range	deg.C	-10~+40			
显示屏使用寿命	Lifetime (50% brightness)	Hour	100,000			